

-  ALL-IN-ONE
-  MOBILITY
-  MODULAR
-  PANELS PC
-  PRINTERS
-  DISPLAYS
-  ACCESSORIES

www.ares.com

YUNO KIOSK 22

compact, multi-application
integrated system



All in one OEM & POS
system for all vertical
kiosk applications

Yuno is a robust and compact equipment, designed by AURES to suit the many applications of the OEM and POS vertical sectors.

This fanless high-performance hardware, fitted with a i3 or Quad-Core Bay Trail platform, is available in a traditional 16:9 21,5" format and equipped with a shock- and scratch-proof, multi-touch, projected, capacitive screen (PCAP technology).

Very flexible, **Yuno Kiosk 22** is offered with VESA fixings options, for easy installation in all kiosks.

The standard version features a 64 GB flash disk (2.5" SSD) and stands up to dirt in the toughest industrial or POS settings (dust, splashes and left-overs...). It integrates an energy efficient Bay Trail J1900 or i3 processor (consuming just 10 W) and

a heat-dissipating aluminium structure, ensuring compliance with environmental standards (low carbon footprint).

Yuno Kiosk 22 is an accessible product whose many features (technology, ergonomics, innovation and design) make it good value for money. It constitutes a sensible, cost-effective and long-term investment for any IT equipment.



YUNO KIOSK 22



Compact, heavy duty but stylish POS terminal
 i3 or Quad-Core Bay Trail J1900 processor
 2.5" 64 GB SSD (2 slots)
 Projected, capacitive, multi-touch screen (PCAP)
 4 GB memory as standard (upgradable to 8 GB)
 Discreet yet easily accessible connectivity
 Mini DP output for 2nd screen
 Energy efficient processor (10 W) and low carbon footprint
 Available with VESA bracket option(s), for wall or pole mounting installations



MODEL YUNO KIOSK 22

Processor	i3 or Bay Trail J1900 Quad-Core
RAM	DDR3 SODIMM 4 GB as standard (up to 8 GB)
SSD	2.5" 64 GB (2 slots)
LCD	21.5" TFT (1920 x 1080) LED back-lighting
Touchscreen	Flat, zero bezel multi-touch screen – with projected, capacitive panel (PCAP)
Brightness	250 cd/m ²

INPUT-OUTPUT PORTS

Serial	3 serial ports (+ 5/12 V power supply for COM3 / COM4)
USB	6 USB 2.0 ports + 3 USB 3.0 port
LAN	10/100/1000Base-T
2nd Screen	Port with support for HDMI, DVI and VGA (mini Display Port)
Audio	Internal loudspeaker, headphones, micro jack plug
Power Supply	+ external 19 V DC
Mini-PCI Express	1 Mini PCI Express slot (WIFI)

MISCELLANEOUS

EMI	CE/FCC Class A
Safety	LVD, external adaptor UL c/us, CE, TUV, etc.
Operating Temperature	0-40 °C
Front	Dust- and splash-proof
Colours	Black or White
Materials	Polycarbonate (cover) + aluminium (structure)
VESA	75 x 75
Dimensions (W x D x H)	517.44 x 54.08 x 313.31 mm
Weight	5.75kg / 7.73kg
Compatible OS	Windows 8.1 Industry Pro, Windows 7 Pro, POSready 7, Linux, Android

OPTIONAL EXTRAS

MSR	3 ISO tracks, OPOS support
RFID / Addimat / Dallas readers	1 slot, at right of EPOS terminal
Fingerprint reader	Yes
Barcode reader	1D and 2D
2nd screen	10.1" - 16:9 1024 x 600 Flat LED screen (EPOS digital signage)
WIFI	Internal, 802.11 b/g/n