



PP180

USB
Ethernet
RS232



Item		CA-PP-2403
Print	Print method	Direct thermal printing
	Resolution	180 x 180DPI
	Print speed	Max. 200mm/s
	Print width	Max. 72mm
	Interface	Standard three interface: serial+USB+Ethernet
	Cash drawer control	1 cash drawer
Barcodes Fonts Graphics	Barcodes	ID:UPC-A, UPC-E, JAN8 (EAN8), JAN13 (EAN13), CODE 39, CODE 93, CODE 128, ITF, CODABAR 2D: PDF417, QR, MAXICOOE, GSI Databar
	Fonts	Font A 12x24. Font B 9x17, kanji 24x24
	Character set	95 Alphanumeric, 13 types of international characters, 128 x 56 Graphic (including user-defined page), Traditional/Simple Chinese, Japanese, Korean (optional)
	Character modification	Rotate (0°, 90°, 180°, 270°), enlarge (1-6x)
	Flash capability	2M / 4M (selectable, according to different font library)
	Flash LOGO	Max. 512Kb
	Data buffer	64Kb, 4Kb, 45 bytes
Paper	Paper type	Continuous paper, Marked paper
	Paper width	57.5/69.5/76/80/82.5mm
	Paper thickness	0.06-0.08mm
	Paper roll OD	83mm {Max.}
	Paper cut	Full cut. Partial cut
Power supply	Input	100-240 VAC, 50-60Hz
	Output	24± 5%V 1.5A
Environment	Operation conditions	5-45-C. 20-90% (40-C)
	Storage conditions	-40-60°C, 20-93% (40-C)
Reliability	Print head lifetime	≥ 150Km
	Cutter lifetime	≥ 1,500,000 cuts (full cut. paper thickness: 0.065mm)
Physics Spec.	Dimensions	145(w) x 195(L) x 141(H)
	Weight	1.45Kg
Standards	Standards	CE. CB, FCC. UL. Energy Star