

LPO-4L

4 x 4 LTE MIMO
Low Profile Antenna

Features

- Low Profile Permanent Mount
- 4 x LTE Elements
- Optional GNSS patch element
- Fully Waterproof when mounted

Specifications

	4 x LTE Elements	Optional GNSS
Frequency range	690-960/1710-2700 MHz	1575.42-1602 MHz
Peak gain	3 / 4 dBi	28dB with LNA (GPS)
Polarisation	Linear	RHCP
VSWR	<2.0:1	<2.0:1
Power rating / Input Power	10 W	DC +2.8~5.0V
Impedance	50 Ohms	50 Ohms
Noise Figure		Max.2.0 (Typical 1.0)
Power Consumption		15 mA (Typical)
Dimensions	140 x 80 mm (dxh)	

Ordering Options

LPO-4L-SM4-20	LPO-4L antenna with 4 x LTE 4 x 20cm RG316 PU cables SMA
LPO-4LG-SM5-20	LPO-4LG antenna with 4 x LTE + GNSS 5 x 20cm RG316 PU cables SMA

Specifications subject to change without notice.

5 Little Balmer
Buckingham Industrial Park
Buckingham
MK18 1TF
UK

Tel: +44 (0)1280 824055
Fax: +44 (0)1280 817179
Email: sales@ead-ltd.com
Web: www.ead-ltd.com

EAD
embedded antenna design ltd