



MP-2L

Magnetic Puck Antenna MIMO LTE

Features

- Low Profile Puck Antenna
- 2 x 4G/LTE Multiband Elements
- High Pull Strength Mag Base
- Side Exit Cables

Specifications

	Element 1	Element 2
Frequency range	690-800/ 800-960 / 1710-2170 / 2500-2700 MHz	690-800/ 800-960 / 1710-2170 / 2500-2700 MHz
Peak Gain	1 / 2.5 / 3.8 / 5 dBi	1 / 2.5 / 3.7 / 5 dBi
VSWR	<3.0:1	<2.5:1
Polarisation	Linear	Linear
Power rating	10 W	10W
Impedance	50 Ohms	50 Ohms
Dimensions	102 x 38mm (dxh)	

Ordering Options

MP-2L-SMSM-1K	MP-2L antenna with 2 x 1M RG174 and SMA-Male
MP-2L-SMSM-2K	MP-2L antenna with 2 x 2M RG174 and SMA-Male
MP-2L-SMSM-3K	MP-2L antenna with 2 x 3M RG174 and SMA-Male

Specifications subject to change without notice.

5 Little Balmer
Buckingham Industrial Park
Buckingham
MK18 1TF
UK

Tel: +44 (0)1280 824055
Fax: +44 (0)1280 817179
Email: sales@ead-ltd.com
Web: www.ead-ltd.com