

Datasheet

SS-2



SS-3



SS-4



SAT SPLITTERS

Features

2 x DC
 Frequency range: 5 - 2300 MHz
 High quality splitter
 Housing approved for outdoor use
 Threaded: F-connector

Technical specifications

Attenuation
 5 - 1000 MHz max. 4.5 dB
 1001 - 1450 MHz max. 5.0 dB
 1451 - 1750 MHz max. 5.4 dB
 1751 - 2050 MHz max. 5.8 dB
 2051 - 2300 MHz max. 6.5 dB

Isolation
 41 - 2300 MHz min. 20 dB

Dimensions and weight:

Unit (WxDxH): 100 x 90 x 50mm
 Unit (Net weight): 0.16 Kg

EAN number: 5706998012098
 Item number: 4882
 Carton QTY: 50

Contents:

Splitter
 Outdoor housing
 Cable tie

Features

3 x DC
 Frequency range: 5 - 2300 MHz
 High quality splitter
 Housing approved for outdoor use
 Threaded: F-connector

Technical specifications

Attenuation
 5 - 40 Mhz min. 12/8 dB
 41 - 1000 MHz max. 7.8 dB
 1001 - 1750 MHz max. 9.5 dB
 1751 - 2050 MHz max. 10.9 dB
 2051 - 2300 MHz max. 11.7 dB

Isolation
 41 - 2300 MHz min. 20 dB

Return loss (in/out)

41 - 1750 Mhz min. 12/10 dB
 1751 - 2300 Mhz min. 15/10 dB

Dimensions and weight:

Unit (WxDxH): 142 x 86 x 45mm
 Unit (Net weight): 0.2 Kg

EAN number: 5706998012104
 Item number: 4883
 Carton QTY: 40

Contents:

Splitter
 Outdoor housing
 Cable tie

Features

4 x DC
 Frequency range: 5 - 2300 MHz
 High quality splitter
 Housing approved for outdoor use
 Threaded: F-connector

Technical specifications

Attenuation
 5-40 MHz max. 8.3dB
 41 - 450 MHz max. 8.5dB
 451-750 MHz max. 8.8dB
 751-1000 MHz max. 9.4dB
 1001 - 1450 MHz max. 10.4dB
 1451 - 1750 MHz max. 11.4dB
 1751 - 2050 MHz max. 12.5dB
 2051 - 2300 MHz max. 13.1dB

Isolation
 5 - 1000 MHz min. 16 dB

Return loss (in/out)
 41 - 1750 Mhz min. 12/10 dB
 1751 - 2300 Mhz min. 15/10 dB

Dimensions and weight:

Unit (WxDxH): 102 x 46 x 17mm
 Unit (Net weight): 0.3 Kg

EAN number: 5706998012111
 Item number: 4884
 Carton QTY: 40

Contents:

Splitter
 Outdoor housing
 Cable tie