

Key Features

A New Angle on Workplace Ergonomics |
Seamless Viewing | Clarity From Any
Angle | Connection Flexibility | Versatile
Stand Design



Product Description

ViewSonic VG2448 is a 24" (23.8" viewable) 1080p monitor with productivity enhancing features including IPS technology and an advanced ergonomic design for the modern day office. Utilising SuperClear® IPS technology and 1080p resolution, VG2448 delivers a crisp, clear image from any viewing angle. An advanced ergonomic design offers the widest range of customisable adjustments currently available to provide maximum comfort, including dual direction pivot, swivel, height adjustment, and an impressive 40° tilt, which enables you to use the monitor while standing and to have strategic group discussions around the screen. VG2448 uses environmentally friendly packaging and offers quick and easy out-of-the-box set-up via the Quick Release stand. The cloud client mountable stand coupled with cable management design features, makes VG2448 perfect for deployment in cloud-based environments. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB 3.0 inputs.



1. VESA Compatible(Wall mount 100mm x 100mm)
2. Menu Control Panel
3. USB down stream x 2
4. AC In
5. DisplayPort
6. HDMI
7. VGA
8. USB up stream
9. USB down stream x 2

LCD PANEL

Monitor Size:	24"W (23.8" Viewable)
Panel Technology:	SuperClear® IPS TFT LCD
Resolution:	FHD 1920 x 1080
Display Area:	527.04 mm (H) x 296.46 mm (V)
Aspect Ratio:	16:9
Brightness:	250 cd/m2 (Typ)
Contrast Ratio:	1000:1 (Typ)
Dynamic Contrast Ratio:	50,000,000:1
Viewing Angle:	178 / 178 (Typ)
Response Time:	5ms (GtG)
Pixel Pitch:	0.2745 (H)mm x 0.2745(V)mm

INPUT SIGNAL

Frequency:	Fh = 24 ~ 82KHz ; Fv = 50 ~ 75Hz
Sync:	Separate Sync / Composite Sync / Sync on Green

COMPATIBILITY

PC:	Windows 7, Windows 8, Windows 10 certified
Mac®:	Power Mac tested

CONNECTOR

Digital:	HDMI x 1 (v1.4 compatible) DisplayPort x 1 (v1.2 compatible)
Analog:	VGA x 1

SPEAKERS

2W x 2

USB

Up Stream:Type B x 1
Down Stream:Type A x 4

POWER

Power:	3-pin plug (CEE22) x 1
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	21W
Optimize:	18W
Conserve:	15W

ERGONOMICS

Tilt:	40 ~ -5 degrees
Swivel:	120 degrees
Pivot:	180 degrees
Height Adjustment:	0 ~ 130mm

WALL MOUNT

VESA®:	100mm x 100mm
--------	---------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm):	549 mm (W) x 517 mm (H) x 202 mm (D)
Physical without stand (mm):	549 mm (W) x 326 mm (H) x 50 mm (D)
Packaging (mm):	604 mm (W) x 385 mm (H) x 210 mm (D)

WEIGHT

Net with stand (kg):	5.82kg
Net without stand (kg):	3.44kg
Gross (kg):	8.71 kg

REGULATIONS

FCC-B, Energy Star 7.0, EPEAT Gold, CE EMC, CB, RoHS Green BOM & RoHS DoC, ErP, REACH SVHC List & DoC, WEEE, TCO 7.0, EAC / CU, UkrSEPRO

PACKAGE CONTENTS

LCD Display
Power Cable
DisplayPort Cable
USB3.0 Upstream Cable
Quick Start Guide

*Actual content may differ from market to market